


- | | |
|--|-------------------------------|
| 1. Power cable entry 4C 10AWG (230Vx3N) or 3C 8AWG (230Vx1-60Hz) | 3. Water loading pipe Ø3/4" G |
| 2. Water drain pipe Ø30 Hmax=45cm | 4. Equipotential |
| | 5. Dosing pumps entry |



- Moulded wash tank with rounded corners and double wall (insulated hood upon request).
- Full-width wash tank filters.
- TOUCH control panel with 5 preset wash cycle times.
- Magnetic microswitch to cut out operation of the appliance when door is opened.
- Useful washing height 41 cm, dish Ø44 cm.
- Square basket 50x50 cm (supplied with 2 plate baskets, 1 flat basket, 2 cutlery holders).
- Independent lower/upper washing and rinsing arms.
- Timed manual cold rinse.
- Washing cycle time 90-120-150-180-210 seconds (capacity 800÷340 pz/h).
- Displays show the boiler and tank temperature.
- Countdown of the washing cycle underway in minutes and seconds.
- Standard built-in rinse-aid pump.
- Standard built-in detergent pump.
- Self-cleaning cycle (CLN).
- Booster pump and built-in insulated atmospheric rinse tank made in AISI 304L stainless steel.
- Boiler and tank heating through thermostatically protected armoured heating elements (in exchange).
- The tank water heating is indirect (heating element is not inside the tank).
- Included drain pump.
- Partial water change each cycle - automatic drain of approx. 3,5 litres of (dirty) water between wash and rinse phase.
- Tank capacity lt. 25 and boiler capacity lt. 13.
- Water consumption per cycle lt. 3,5 - Water pressure input ATE 2,0-3,0 - Max temperature of inlet water 50°C.
- Tank heating element kW 3,0 - Boiler heating element kW 6,0
- Washing pump power Hp 1,2.
- Booster pump power kW 0,19.
- Noise level at 1 mt. < 70 dbA.
- Total power kW 6,90.
- Current draw: 17.5 A (230Vx3N), 30 A (230Vx1N)
- Automatic start on hood closing.

Note

Can be used in straight-line and corner installations in combination with prewash inlet tables and outlet tables.