

Features

- HC refrigerant
- CFC free refrigerant and foam
- Electronic thermostat and digital LED temperature display for accurate control and easy reading
- Self-closing door
- Magnetic gasket can be replaced without any tool
- Low-e triple pane glass doors
- INTERIOR: Powder-coated steel white
- EXTERIOR: Powder-coated steel white , Plastic top sign panel with lamp



R1G-25-WS / F1G-25-WS



R1G-26-WS / F1G-26-WS



R1G-27-WS / F1G-27-WS





R1G-28-WS / F1G-28-WS

MODEL	EXTERNAL DIMENSION inch	V/Hz/Ph	NET STORAGE CAPACITY Cu-ft	TEMPERATURE	NEMA PLUG
R1G-25-WS	25 × 26 × 61 ^{13/16}	115V/60Hz/1	12	33°F—41°F	5-15P
R1G-26-WS	25 × 26 × 74 ^{13/16}	115V/60Hz/1	16	33°F—41°F	5-15P
R1G-27-WS	26 ^{3/4} × 31 ^{7/8} × 79 ^{1/2}	115V/60Hz/1	23	33°F—41°F	5-15P
R1G-28-WS	28 ^{3/8} × 33 ^{7/8} × 79 ^{1/2}	115V/60Hz/1	23	33°F—41°F	5-15P
R2G-40-WS	39 ^{1/2} × 32 ^{1/16} × 79 ^{1/2}	115V/60Hz/1	35	33°F—41°F	5-15P
R2G-54-WS	53 ^{15/16} × 31 ^{7/8} × 79 ^{1/2}	115V/60Hz/1	48	33°F—41°F	5-15P
R3G-81-WS	81 × 31 ^{7/8} × 79 ^{1/2}	115V/60Hz/1	72	33°F—41°F	5-15P





Certified To ANSI/NSF 7 Standards



◆ R1G-25-WS / F1G-25-WS



◆ R1G-26-WS / F1G-26-WS



◆ HR1G-27-WS / F1G-27-WS



◆ R1G-28-WS / F1G-28-WS

